



### Material Specifications

Frequency Range	DC – 18 GHz
VSWR	
DC – 4 GHz	1.04:1 Max.
4 – 8 GHz	1.07:1 Max.
8 – 18 GHz	1.12:1 Max.
Impedance	50 Ohms
Operating Temp Range	-65°C to +125°C
Type N Connectors	Passivated Stainless Steel
(Mates with MIL-STD-348)	
Conductors	Gold Plated Beryllium Copper



<b>Federal Custom Cable</b> <a href="http://www.FCCable.com">www.FCCable.com</a>  1891 Alton Parkway, Irvine, CA 92606 Phone: (949) 851-3114   Fax: (949) 852-8136 <a href="mailto:Sales@FCCable.com">Sales@FCCable.com</a>	<b>CAGE CODE</b> 1UKX3	<b>Part Number:</b> <b>PA1468</b>	<b>Description:</b> <b>N FEMALE TO N FEMALE PANEL MOUNT          PRECISION ADAPTER</b>
	<b>Dimensions</b> Millimeters   Inches		
	<b>Scale:</b> N/A	<b>NOTES:</b> 1. DIMENSIONS ARE IN MILLIMETERS   INCHES 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE	THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.
	<b>Revision:</b>		