



1. FREQUENCY RANGE: DC-2.5 GHz
2. VSWR: 1.2 MAX.
3. DIELECTRIC WITHSTANDING VOLTAGE: 2500 VRMS, MIN.
3. DURABILITY: 500 CYCLES MIN.
4. TEMPERATURE RANGE: -65°C TO +165°C
5. CRIMPED FERRULE
HEX. CRIMP SIZE .178"
6. CONTACT PIN TO SOLDER

Material Specifications

Cable(s): RG174, 188A, 316, B7805A
 Body: Brass
 Finish: White Bronze
 Insulation: Teflon
 Impedence: 50 Ohms



Federal Custom Cable
www.FCCable.com
 1891 Alton Parkway, Irvine, CA 92606
 Phone: (949) 851-3114 | Fax: (949) 852-8136
Sales@FCCable.com

CAGE CODE
1UKX3

Dimensions
Millimeters | Inches

Scale: N/A

Revision:

Part Number:
C1552

Description:
**N MALE CONNECTOR RIGHT ANGLE CRIMP FOR
RG174, RG188, RG316, B7805A CABLES**

NOTES:
 1. DIMENSIONS ARE IN MILLIMETERS | INCHES
 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL
 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.