


SUGGESTED STRIPPING INSTRUCTIONS
SUGGESTED CRIMP DIES: .100 & .213

Material Specifications

Cable(s): RG55,142,223,400
Body: Brass
Finish: Silver
Insulation: Teflon
Impedence: 50 Ohms



| | | | | |
|---|---|--|---|--|
|  Federal Custom Cable www.FCCable.com 1891 Alton Parkway, Irvine, CA 92606 Phone: (949) 851-3114 Fax: (949) 852-8136 Sales@FCCable.com | CAGE CODE 1UKX3 | Part Number: <h1>C1636</h1> | Description: N MALE CONNECTOR QUICK DISCONNECT CRIMP FOR RG142, RG223, RG400 CABLES | |
| | Dimensions Millimeters Inches | | | |
| | Scale: N/A | NOTES: 1. DIMENSIONS ARE IN MILLIMETERS INCHES 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE | THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC. | |
| | Revision: | | | |