



CAGE CODE

Revision:





RECOMMENDED CABLE STRIPPING DIMENSIONS

Material Specifications

.085 SEMI-RIGID, 405/U Cable(s):

Body: Brass Finish: Gold Insulation: Teflon Impedence: 50 Ohms





Federal Custom Cable www.FCCable.com

1891 Alton Parkway, Irvine, CA 92606 Phone: (949) 851-3114 | Fax: (949) 852-8136

Sales	@FC	Cabl	e.con
-------	-----	------	-------

1UKX3	COFOC	MCX PLUG CONNECTOR SOLDER FOR RG405,		
Dimensions Millimeters I Inches	C2526	RG405AL, RG405FL CABLES		
Scale: N/A	NOTES: 1. DIMENSIONS ARE IN MILLIMETERS II	NCHES	THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PRO-	

Part Number

3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

BELONGS TO FEDERAL VING IS PROHIBITED WITHOUT 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL WTITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. © 2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.

Description: