



RECOMMENDED CABLE STRIPPING DIMS.

NOTE:

1. CONTACT PIN TO SOLDER
2. MAX. PANEL THICKNESS = 2.4mm



Material Specifications

Cable(s): .085 SEMI-RIGID, 405/U
 Body: Brass
 Finish: Gold
 Insulation: Teflon
 Impedence: 50 Ohms

FCC Federal Custom Cable
www.FCCable.com
 1891 Alton Parkway, Irvine, CA 92606
 Phone: (949) 851-3114 | Fax: (949) 852-8136
Sales@FCCable.com

CAGE CODE 1UKX3	Part Number: C2559	Description: SMA FEMALE CONNECTOR BULKHEAD SOLDER FOR RG405, RG405AL, RG405FL CABLES
Scale: N/A	NOTES: 1. DIMENSIONS ARE IN MILLIMETERS INCHES 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE	THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.
Revision:		