







RECOMMENDED CABLE STRIPPING DIM'S

## **Material Specifications**

Cable(s): .085 SEMI-RIGID, 405/U

Body: Brass Gold Finish: Insulation: Teflon Impedence: 50 Ohms





## **Federal Custom Cable** www.FCCable.com

1891 Alton Parkway, Irvine, CA 926 Phone: (949) 851-3114 | Fax: (949) 85 Sales@FCCable.com

2606 852-8136	
	l

Scale:

Revision:

CAGE CODE	Part Number:
1UKX3	

C2578 **Dimensions** Millimeters I Inches

## **Description:**

## SMB PLUG CONNECTOR SOLDER FOR RG405, RG405AL, RG405FL CABLES

NOTES: N/A

1. DIMENSIONS ARE IN MILLIMETERS | INCHES

2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WTITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. © 2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.