



NOTES:

1. CONTACT PIN TO SOLDER
2. MAX. PANEL THICKNESS = 6.8mm

**Material Specifications**

Cable(s): .085 SEMI-RIGID, 405/U  
 Body: Brass  
 Finish: Gold  
 Insulation: Teflon  
 Impedence: 50 Ohms



**Federal Custom Cable**  
[www.FCCable.com](http://www.FCCable.com)  
 1891 Alton Parkway, Irvine, CA 92606  
 Phone: (949) 851-3114 | Fax: (949) 852-8136  
[Sales@FCCable.com](mailto:Sales@FCCable.com)

|                                    |     |
|------------------------------------|-----|
| CAGE CODE<br>1UKX3                 |     |
| Dimensions<br>Millimeters   Inches |     |
| Scale:                             | N/A |
| Revision:                          |     |

Part Number:  
**C2660**

NOTES:  
 1. DIMENSIONS ARE IN MILLIMETERS | INCHES  
 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL  
 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Description:  
**MCX JACK CONNECTOR BULKHEAD SOLDER MNTG  
 FIG. D-2 FOR RG405, RG405AL, RG405FL CABLES**

THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.