



1. FREQUENCY RANGE: DC 0–12.4 GHZ
2. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.
3. DURABILITY: 500 CYCLES MIN.
4. TEMPERATURE RANGE: –65°C TO +165°C
5. CRIMPED FERRULE
6. HEX. CRIMP SIZE .128 CONTACT PIN TO SOLDER

Material Specifications

Cable(s): RG178/196
 Body: Brass
 Finish: Gold
 Insulation: Teflon
 Impedence: 50 Ohms



Federal Custom Cable
www.FCCable.com
 1891 Alton Parkway, Irvine, CA 92606
 Phone: (949) 851-3114 | Fax: (949) 852-8136
Sales@FCCable.com

CAGE CODE 1UKX3
Dimensions Millimeters Inches
Scale: N/A
Revision:

Part Number:
C3037RP

Description:
SMA REVERSE POLARITY MALE CONNECTOR RIGHT ANGLE CRIMP FOR RG178, RG196 CABLES

NOTES:
 1. DIMENSIONS ARE IN MILLIMETERS | INCHES
 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL
 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.