



| Materia | al Specifications | 1. CONTACT PIN TO SOLDER |
|-------------|------------------------|--------------------------|
| Cable(s): | .085 SEMI-RIGID, 405/U | AD FREE |
| Body: | Brass | |
| Finish: | Gold | Конэ |
| Insulation: | Teflon | |
| Impedence: | 50 Ohms | TNALISH |
| | | |

| | Federal Custom Cable www.FCCable.com | CAGE COD 1UKX3 |)E | Part Number: | Description: SMA REVERSE POLARITY FEMALE CONNECTOR | |
|---|---|-------------------------------|-----|---|---|--|
| 1891 Alton Parkway, Irvine, CA 92606 Phone: (949) 851-3114 I Fax: (949) 852-8136 Sales@FCCable.com | | Dimension Millimeters I II | | C3614RP | SOLDER FOR RG405, RG405AL, RG405FL CABLES | |
| | | Scale: | N/A | NOTES: 1. DIMENSIONS ARE IN MILLIMETERS 1 INCHES 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE | | THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT |
| | | Revision: | | | | WTITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED.©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC. |