



- NOTES:
1. MEETS STANDARD N SERIES INTERFACE DIMENSIONS PER MIL-STD-348
 2. FREQUENCY RANGE: DC 0-11 GHZ
 3. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS, MIN.
 4. DURABILITY: 500 CYCLES, MIN.
 5. TEMPERATURE RANGE: -65°C TO +165°C

Material Specifications

Cable(s):	N/A
Body:	Brass
Finish:	Nickel
Insulation:	Teflon
Impedence:	50 Ohms



Federal Custom Cable
www.FCCable.com
1891 Alton Parkway, Irvine, CA 92606
Phone: (949) 851-3114 | Fax: (949) 852-8136
Sales@FCCable.com

CAGE CODE 1UKX3
Dimensions Millimeters Inches
Scale: N/A
Revision:

Part Number:
C5763

NOTES:
1. DIMENSIONS ARE IN MILLIMETERS | INCHES
2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL
3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Description:
N FEMALE CONNECTOR PRINTED CIRCUIT BOARD RECPTACLE

THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.