


RECOMMENDED CABLE STRIPPING DIMENSIONS

**Material Specifications**

Cable(s): .085 SEMI-RIGID, 405/U  
 Body: Brass  
 Finish: Gold  
 Insulation: Teflon  
 Impedence: 50 Ohms



|   |   |  |   |
|---|---|--|---|
|  <b>Federal Custom Cable</b><br>www.FCCable.com<br>1891 Alton Parkway, Irvine, CA 92606<br>Phone: (949) 851-3114   Fax: (949) 852-8136<br>Sales@FCCable.com | <b>CAGE CODE</b><br>1UKX3                 | <b>Part Number:</b><br><br><b>C5791</b>  | <b>Description:</b><br><b>SMB PLUG CONNECTOR RIGHT ANGLE SOLDER FOR RG405, RG405AL, RG405FL CABLES</b>  |
|   | <b>Dimensions</b><br>Millimeters   Inches |  |   |
|   | <b>Scale:</b> N/A                         | <b>NOTES:</b><br>1. DIMENSIONS ARE IN MILLIMETERS   INCHES<br>2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL<br>3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE | THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC. |
|   | <b>Revision:</b>                          |  |   |