









- IMPEDANCE: 50 OHM
- 1. IMPEDANCE: 50 OHM
  2. FREQUENCY RANGE: DC 0-6 GHz
  3. DIELECTRIC WITHSTANDING VOLTAGE: 2300 VRMS
  4. DURABILITY: 500 CYCLES MIN.
  5. TEMPERATURE RANGE: -65°C to +165°C
  6. CRIMPED FERRULE
  HEX CRIMP SIZE .429"

# **Material Specifications**

B9913, LMR400, B7810A, B8214 Cable(s):

Body: Brass Finish: Nexcote Insulation: Teflon 50 Ohms Impedence:





# **Federal Custom Ca** www.FCCable.com

1891 Alton Parkway, Irvine, CA 92606 Phone: (949) 851-3114 | Fax: (949) 852-8136 Sales@FCCable.com

able	
m	

# **Dimensions** Millimeters I Inches

CAGE CODE

1UKX3

Scale: Revision:

### **Part Number:**

C6016

#### **Description:**

7/16 DIN FEMALE CONNECTOR PANEL MOUNT CRIMP FOR B9913, LMR400, B7810A, B8215 CABLES

NOTES:

1. DIMENSIONS ARE IN MILLIMETERS | INCHES

2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT BELONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT WTITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. © 2016 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.