6.5 [.256] — 20 [.788]

RECOMMENDED
CABLE STRIPPING DIM'S

Ø2.5 [Ø.098](4X)

M29XP1.5

24.8 [.977]

24.8 [.977]

32 [1.261]

44.8 [1.765]

26 [1.024]

6.5 [.256]

Material Specifications

Cable(s):   ANDREWS 0.5IN SUPER FLEX

Finish: Silver

Insulation: Teflon

Impedance: 50 Ohms

RoHS LEAD FREE COMPLIANT

Federal Custom Cable
www.FCCable.com

1891 Alton Parkway, Irvine, CA 92606
Phone: (949) 851-3114 I Fax: (949) 852-8136
Sales@FCCable.com

CAGE CODE 1UKX3	Part Number:	Description:
	C6205	**7/16 DIN FEMALE CONNECTOR PANEL MOUNT**
Dimensions Millimeters I Inches		**CLAMP 0.5IN SUPER FLEX FOR ANDREWS CABLES**

Scale:	N/A	NOTES:
Revision:		1. DIMENSIONS ARE IN MILLIMETERS I INCHES 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE