





Material Specifications

NOTES

1.Material & Finishing

Body: Stainless Steel TYPE 303, Passivate

Insulators: PTFE

Center Conductor: Beryllium Copper Gold Plating

2.Electrical Data: Impedance: 50 Ohms Frequency: DC~18GHz

VSWR

DC~18GHz----1.25Max.

Revision:





Federal Custom Cable www.FCCable.com

1891 Alton Parkway, Irvine, CA 92606 Phone: (949) 851-3114 | Fax: (949) 852-8136 Sales@FCCable.com

| | CAGE CODE 1UKX3 | Part Number: | PUSH ON SMA MALE TO SMA FEMALE BULKHEAD | | |
|--|----------------------|---|---|--|--|
| | | PA1671 | | | |
| | Dimensions | Dimensions | | PRECISION ADAPTER DC-18GHZ | |
| | Millimeters I Inches | | | | |
| | Scale: N/A | NOTES: 1. DIMENSIONS ARE IN MILLIMETERS INCHES | | THIS DRAWING CONTAINS PROPRIETART INFORMATION THAT BELONGS TO F CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHI | |

3. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

LONGS TO FEDERAL CUSTOM CABLE, LLC. ANY UNAUTHORIZED USE OF THIS DRAWING IS PROHIBITED WITHOUT 2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL WRITTEN PERMISSION FROM FEDERAL CUSTOM CABLE. ALL RIGHTS RESERVED. ©2020 COPYRIGHT FEDERAL CUSTOM CABLE, LLC.